

Specifications for Repair of the Irion County Courthouse Roof

Description	Quantity
1. R&R Modified Bitumen Roof	42.53 SQ
2. R&R Built Up Roof – Additional Glass Felt Layer	212.67 SQ
3. R&R Insulation – ISO Board, 1”	42.53 SQ
4. R&R Flash Parapet Wall Only – Bitumen	314 LF
5. Flashing – Pipe Jack – Lead	10 EA
6. R&R Membrane Roofing – Cant Strips – Perlite	314 LF
7. Exhaust Cap – Through Roof – 6” to 8”	1 EA
8. R&R Pitch Pan / Pocket Up to 6” x 6” x 4” – Galvanized	1 EA
9. Install Gravity Roof Ventilator – 18”	3 EA
10. Roof Drain Cover – Detach & Reset	2 EA
11. Install Exhaust Fan – Commercial	1 EA
12. Electrician – Per Hour Labor to Detach & Reset Conduit	5 HR
13. Crane & Operator – 50 Ton Capacity	30 HR
14. Debris Chute Hopper – Per Week – 30” x 4’ section Eleven Sections for Three (3) Weeks	33 HR
15. Debris Chute Mounting Hardware – Per Week	2 WK
16. General Laborer – Per Hour 4 Men x 4 Hours Each x 2 (set up and take down)	32 HR
17. Commercial Supervision / Project Management – Per Hour	40 HR